



Suspension luminaire with diffuse light for indoor use.

The soft light of opaline glass.

In CALMA UP&DOWN, a small luminous sphere is moved up and down from the ceiling by a sophisticated control system. In CALMA S, the available roses are in textured matt black or matt white painted steel. In CALMA UP&DOWN, the rose is in sanded black anodised aluminium. The glass support comes in a range of painted or galvanised finishes. The opaline ball is in triple-layer blown glass. The luminaire is also available in the wall and table version.

The light source is LED with integrated module. In CALMA S, the electric cable is coaxial and in matt white or matt black, depending on the luminaire finish. A range of roses and power supplies are available. In CALMA UP&DOWN, the electric cable is coaxial and matt black and can be adjusted using an automatic winder.

Apparecchio di illuminazione a sospensione, a luce diffusa, per interni.

La luce morbida del vetro opalino.

In CALMA UP&DOWN, una piccola sfera luminosa sale e scende dal soffitto grazie ad un sofisticato sistema di regolazione. In CALMA S, i rosoni disponibili sono in acciaio verniciati bianco opaco o nero opaco texturizzato. In CALMA UP&DOWN, il rosone è in alluminio anodizzato nero opaco sabbiato. Il supporto del vetro è in ottone in varie finiture verniciate o galvanizzate. Il vetro sferico è opalino e in triplo strato soffiato. L'apparecchio è disponibile anche in versione da parete e da tavolo.

La sorgente luminosa è a LED e a modulo integrato. In CALMA S, il cavo elettrico è coassiale e di colore bianco opaco o nero opaco in funzione della finitura. Sono disponibili vari rosoni e sistemi di alimentazione. In CALMA UP&DOWN, il cavo elettrico è coassiale e di colore nero opaco e può essere regolato tramite un avvolgitore automatico.

|               |                          |               |                        |               |
|---------------|--------------------------|---------------|------------------------|---------------|
| <b>Finish</b> | <b>.03</b> Matt White    | (White cable) | <b>.04</b> Matt Black  | (White cable) |
|               | <b>.19</b> Polished Gold | (Black cable) | <b>.26</b> Total Black | (Black cable) |
|               | <b>.45</b> Matt Nickel   | (Black cable) |                        |               |

**Certification**

Luminaire available for US/CAN market. Available for CHINA market.

Apparecchio illuminante disponibile per mercato US/CAN. Disponibile per mercato CHINA.




**CALMA S**

4W  
 Max 350mA DC  
 2700K - 150lm / 3000K - 160lm  
 CRI >90  
 Driver not included  
 CE IP20

|                       |                 |
|-----------------------|-----------------|
| Matt White - 2700K    | 1A6890300.27.20 |
| Matt White - 3000K    | 1A6890300.30.20 |
| Matt Black - 2700K    | 1A6890400.27.20 |
| Matt Black - 3000K    | 1A6890400.30.20 |
| Polished Gold - 2700K | 1A6891900.27.20 |
| Polished Gold - 3000K | 1A6891900.30.20 |
| Total Black - 2700K   | 1A6892600.27.20 |
| Total Black - 3000K   | 1A6892600.30.20 |
| Matt Nickel - 2700K   | 1A6894500.27.20 |
| Matt Nickel - 3000K   | 1A6894500.30.20 |

**Compulsory accessories / Accessori obbligatori**

Suspension kits / Kit di sospensione



| Ceiling rose with driver / Rosone con alimentatore |  | Not included    |
|--|--|-----------------|
| Matt White   | Input 110-240V - 50/60Hz<br>Output 350mA DC - Max 4W<br>IP20 - DALI - PUSH - 1-10V | 1X0290300.02.07 |
| Matt Black   | Input 110-240V - 50/60Hz<br>Output 350mA DC - Max 4W<br>IP20 - DALI - PUSH - 1-10V | 1X0290400.02.07 |
| Matt White   | Input 220-240V - 50/60Hz<br>Output 350mA DC - Max 4W<br>IP20 - TRIAC/IGBT          | 1X0290300.02.02 |
| Matt Black   | Input 220-240V - 50/60Hz<br>Output 350mA DC - Max 4W<br>IP20 - TRIAC/IGBT          | 1X0290400.02.02 |



| Ceiling rose without driver / Rosone senza alimentatore |                                 | Not included    |
|---|---------------------------------|-----------------|
| Matt White  | For electrical cables - 1 Piece | 1X0010300.04.00 |
| Matt Black  | For electrical cables - 1 Piece | 1X0010400.04.00 |




| Recessed rose without driver / Rosone da incasso senza alimentatore |   | Not included    |
|---|---|-----------------|
| Matt White  | For electrical cables - 1 Piece<br>Plasterboard cut-out Ø 44 mm<br>Minimum space for mounting 70 mm<br>For 12,5 mm plasterboard | 1X0000300.04.00 |
| Matt Black  | For electrical cables - 1 Piece<br>Plasterboard cut-out Ø 44 mm<br>Minimum space for mounting 70 mm<br>For 12,5 mm plasterboard | 1X0000400.04.00 |


The sizes are expressed in millimeters.

**Compulsory accessories / Accessori obbligatori**

Drivers / Alimentatori




| Driver / Alimentatore |                           | Not included  |
|-----------------------|---------------------------|---------------|
| 220-240V              | 350mA/17W/IP20/TRIAC/IGBT | 1Z0240850.350 |




| Driver / Alimentatore |   | Not included  |
|-----------------------|---|---------------|
| 220-240V(110-127V)    | 350mA/18,9W(13,5W)/IP20/DALI - PUSH - 1-10V | 1Z0241270.350 |

**Optional accessories / Accessori opzionali**


Suspension kits / Kit di sospensione



| Decentralization kit / Kit decentratore |  | Not included    |
|---|--|-----------------|
|   |  | 1A0360000.00.00 |



| Kit ceiling rose and decentralizer / Kit rosone e decentratore |                                | Not included    |
|--|--------------------------------|-----------------|
| Matt White   | Transparent cable 3 m included | 1A0770300.00.00 |
| Matt Black   | Transparent cable 3 m included | 1A0770400.00.00 |




**CALMA UP&DOWN 1**

Ceiling driver version  
5W  
220-240V - 50/60Hz  
2700K - 150lm / 3000K - 160lm  
CRI >90  
Driver integrated  
TRIAC/IGBT

CE IP20

|                                    |                 |
|------------------------------------|-----------------|
| Polished Gold - 2700K - TRIAC/IGBT | 1A7051900.27.02 |
| Polished Gold - 3000K - TRIAC/IGBT | 1A7051900.30.02 |
| Total Black - 2700K - TRIAC/IGBT   | 1A7052600.27.02 |
| Total Black - 3000K - TRIAC/IGBT   | 1A7052600.30.02 |




**CALMA UP&DOWN 1**

Ceiling driver version  
5W  
220-240V - 50/60Hz  
2700K - 150lm / 3000K - 160lm  
CRI >90  
Driver integrated  
DALI - PUSH

CE IP20

|                                     |                 |
|-------------------------------------|-----------------|
| Polished Gold - 2700K - DALI - PUSH | 1A7051900.27.08 |
| Polished Gold - 3000K - DALI - PUSH | 1A7051900.30.08 |
| Total Black - 2700K - DALI - PUSH   | 1A7052600.27.08 |
| Total Black - 3000K - DALI - PUSH   | 1A7052600.30.08 |



**CALMA UP&DOWN 2**


Remote driver version  
4W  
Max 350mA DC  
2700K - 150lm / 3000K - 160lm  
CRI >90  
Driver not included

CE IP20


|                       |                 |
|-----------------------|-----------------|
| Polished Gold - 2700K | 1A7051900.27.20 |
| Polished Gold - 3000K | 1A7051900.30.20 |
| Total Black - 2700K   | 1A7052600.27.20 |
| Total Black - 3000K   | 1A7052600.30.20 |

**Compulsory accessories / Accessori obbligatori**

Drivers / Alimentatori



| Driver / Alimentatore |                           |                 |               | Not included |
|-----------------------|---------------------------|-----------------|---------------|--------------|
| 220-240V              | 350mA/17W/IP20/TRIAC/IGBT | CALMA UP&DOWN 2 | 1Z0240850.350 |              |



| Driver / Alimentatore |   |                 |               | Not included |
|-----------------------|---|-----------------|---------------|--------------|
| 220-240V(110-127V)    | 350mA/18,9W(13,5W)/IP20/DALI - PUSH - 1-10V | CALMA UP&DOWN 2 | 1Z0241270.350 |              |